



# SMALL BLOCK MODIFIEDS RULES

**MANDATORY WEIGHT CLASS ENGINE PACKAGE MUST HAVE WEIGHT DISPLAYED ON BOTH LEFT AND RIGHT SIDE OF HOOD.**

## 1. ENGINES:

Option 1: Ported Steel Heads 23 degree maximum open intake & exhaust – 2600 lbs TSP

Option 2: Non Ported Brodix Spec Heads, open intake or exhaust – 2450 lbs TSP  
(Ford and Chrysler)

Option 3: Brodix Non Ported Spec Heads, Spec Intake with Schoenfeld Spec Exhaust – 2350 lbs TSP

Option 4: **OCFS ONLY!!!** GM CT 525 Crate Engine, Part # 19171821 will be allowed.  
**NOTE:** This Engine must remain stock sealed O.E.M. This engine must also Run with the O.E.M. electronic controller part # 19171130  
2350 lbs TSP aluminum engine with or without Tri Y, optional exhaust.

W16 ENGINE PACKAGE WILL BE INTRODUCED AT 2275 lbs TSP, optional exhaust  
All weight packages may be adjusted in one (1) weeks' notice.

## COMPRESSION RATIO:

\*10.5 Maximum on both spec heads.

\*Open Compression on ported steel headed engines

\*Titanium Valves allowed on Option 1 ONLY!!!

## 2. HEADERS:

**GM CRATE CT525 and W16 ENGINE.**

1. Schoenfeld Part # 1124VY, 1124VYLS1, 1124VLS1, 1124VLS1-3
2. BEYEA Part# NEDMSB-525US-D1, NEDMSBTY-525US-D1, NEDMSBTYUS-LS2

**358 DIVISION FULL SPEC**

1. Chevy: Schoenfeld Part # 1122BV, 1122BVSH-3, 1122BVUSH-3, 1124BV, 1124BVU
2. Ford: Schoenfeld Part # 3122B, 3122BU
3. Mopar: Schoenfeld Part # 4122B, 4122BU

**358 DIVISION FULL SPEC BEYEA PART #'s**

1. NEDMSB-S1-DL, NEDMSBUS-S1-DL, NEDMSB-S2-DL, NEDMSBUS-S2-DL

**358 DIVISION PORTED INTAKE**

1. Schoefeld Part # 1122VY, 1124 VY
2. BEYEA Part #NEDMSBTYUS-D1-3, NEDMSBTYUS-S2-3, NEDMSBTYUS-S2-3.5

**All 358 engine packages Henry exhaust is legal part #DMMMS3 & DMMS4.**

NOTE--- All Spec motors must have a 9" minimum deck height. This will be measured the center of crankshaft to top of block surface. \*\*Should any of these Options prove to have an unfair advantage in the class, total weights may need to be adjusted as needed.

1. Must have an MSD ignition, No Magneto. Magneto will be legal Eastern States Weekend. NO TRIGGER IGNITION except Option 4 at OCFS
2. **Carburetor must be Holley, base and bowls 4150 Series, not to exceed 650 CFM only with the exception of the W16 Engine package. Must run a 4150 series Holley base and bowl CFM optional. All carburetor packages may be adjusted in one (1) week's notice.**
3. **Carburetor's will be tested with go/no go gauge.**
4. Spark Box (Rev Limiter) Optional
5. NO DRY SUMP ENGINES!!
6. VP Racing Fuel or pump gas ONLY!! No additives.
7. Your option weight designation need to be visibly displayed on both sides of the cowl. Wrong weight class designation will result in disqualification.

**GEAR RULE (Not to exceed):**

Ported Steel Heads – 5:44      Both Spec Heads – 5:57      W16 Engine -5:50  
 525 Engine Package – 5:20  
 Gear rule may be adjusted in one (1) week's notice.

**TRANSMISSION:**

Input at engine to output at driveshaft must be the same one to one final ratio.

**BORE and STROKE SPECIFICATIONS:**

CHEVY – 350 c.i. 4.00" Bore x 3.489" Stroke Maximum Overbore = .070" =363 c.i.  
 Chrysler - 360 c.i. 4.00" Bore x 3.578" Stroke Maximum Overbore = .020" =364 c.i.  
 Chrysler - 340 c.i. 4.04" Bore x 3.313" Stroke Maximum Overbore = .060" = 350 c.i.  
 Ford - 351 c.i. 4.00" Bore x 3.500" Stroke Maximum Overbore = .060" = 363 c.i.

These are the ONLY four (4) cast Iron Blocks permitted! NO ALUMINUM –Exc Option 4 OCFS  
 OEM Chevy and Bowtie Performance Block, OEM Chrysler and R Performance Block,  
 OEM Ford and SVO Performance Block, Dart Performance (Little M) and SHP Block

**INTAKE MANIFOLDS ALLOWED:** Must be cast aluminum one (1) piece single plane Only! No matching porting, welding or epoxy of any kind for running the 2350 lbs weight option. Any American manufactured intake made one (1) piece cast aluminum single plane manifold will be legal for the 2450 and 2600 weight options. Ported intake allowed. No welding or epoxy allowed.

CHEVY 350 c.i. Part# HV1000 Brodix or older version HV1  
 Chrysler 360 c.i. & 340 c.i. Part# 2915 Edelbrock or stock OEM Part# P-4876829SR  
 FORD 351 c.i. Part# Edelbrock 9.5" deck height and Part# 2980 9.2" deck.

**TIRES:**

ONLY HOOSIER Racing Tires will be allowed, the following compound designation for tires:  
 D400 (Dirt Hard) D500 optional right rear (Dirt Extra Hard)  
 Tire Size & Compound Designation:  
 Front – 11/82-15 or 13/82-15  
 Rear – 13/87-15, 13/89-15 or 13/92-15

Anyone caught cheating will lose parts that have been deemed illegal and will be penalized points and possibly fined at the discretion of OCFS Management.